



801AUTO



9A06



603

Auto / Manual, 3¾ Digit, 3999 Count LCD, with APO, Capacitance, Frequency, Duty Cycle & Temperature

Ranges	
DC Voltage	400mV/4/40/400/1000V
Accuracy	± (0.5%rdg + 4 dgt) on 400mV/4V ± (0.7%rdg + 4 dgt) on 40/400V ± (1.0%rdg + 4 dgt) on 1000V
AC Voltage	4/40/400/750V
Accuracy	± (1.0%rdg + 5 dgt) on all ranges except ± (1.5%rdg + 8 dgt) on 750V
DC Current	400/4000µA/40/400mA/4/20A
Accuracy	± (1.5%rdg + 4 dgt)
AC Current	400/4000µA/40/400mA/4/20A
Accuracy	± (2.2%rdg + 4 dgt)
Resistance	400Ω/4/40/400kΩ/4/40MΩ
Accuracy	± (0.7%rdg + 4 dgt) on all ranges except ± (1.2%rdg + 4 dgt) on 4MΩ ± (2.5%rdg + 4 dgt) on 40MΩ
Capacitance	40/400nF/4/40/100µF
Accuracy	± (5.0%rdg + 10 dgt)
Frequency	9.999Hz ~ 9.999MHz
Accuracy	± (0.5%rdg + 2 dgt)
Duty Cycle	0.1% ~ 99.9%
Accuracy	± (0.5%rdg + 2 dgt)
Temperature	-20°C ~ 1300°C
Accuracy	± (2%rdg + 4 dgt) (with appropriate sensor to be procured separately)
Sp. Function	Diode Test, Audible Contunity, Data Hold
Power	Two 1.5V Battery Eveready Type 1015 or equivalent
Low Battery	"" is indicated
Battery Life	200 hours typical
Dimensions	161(H) x 86(W) x 33(D) mm
Weight	275 gms approx.
Accessories	Supplied with pair of test leads, battery, K type thermocouple (upto 260°C), instruction manual & carrying case

Auto / Manual, 3½ Digit, 1999 Count LCD, with APO & Temperature

Ranges	
DC Voltage	200mV/2/20/200/1000V
Accuracy	± (0.5%rdg + 4dgt) on 200mV & 2V, ± (0.7%rdg + 4dgt) on 20V & 200V, ± (1%rdg + 4dgt) on 1000V
AC Voltage	200mV/2/20/200/750V
Accuracy	± (1.0%rdg + 8dgt) on all ranges except ± (1.5%rdg + 8dgt) on 750V
DC Current	200/2000µA/20/200mA/10A
Accuracy	± (1.5%rdg + 4dgt)
AC Current	200/2000µA/20/200mA/10A
Accuracy	± (2.2%rdg + 4dgt)
Resistance	200Ω/2/20/200kΩ/2/20MΩ
Accuracy	± (0.7%rdg + 4dgt) on all ranges except ± (1.2%rdg + 4dgt) on 2MΩ ± (2.5%rdg + 4dgt) on 20MΩ
Temperature	-20°C ~ 1300°C/-4°F ~ 1999°F
Accuracy	± (2%rdg + 4dgt) (with appropriate sensor to be procured separately)
Sp. Function	Diode Test, Audible Contunity, Data Hold
Power	Two 1.5V Battery Eveready Type 1015 or equivalent
Low Battery	"" Indicated
Battery Life	200 hours typical
Dimensions	161(H) x 86(W) x 33(D)mm
Weight	275 gms approx.
Accessories	Supplied with pair of test leads, battery, K type thermo couple (upto 260°C), inst. manual & carrying case

3½ digit 1999 Count LCD 17mm Large LCD with Audiable Continuity, Diode & HFE Test

Ranges	
DC Voltage	200mV/2/20/200/1000V
Accuracy	± (0.5%rdg + 1dgt) on all ranges
AC Voltage	200mV/2/20/200/750V (50-500Hz)
Accuracy	± (1%rdg + 4dgt) on all ranges except ± (1.5%rdg + 4dgt) on 750V
DC Current	200µA/2mA/20mA/200mA/20A
Accuracy	± (1%rdg + 1dgt) on all ranges except ± (2%rdg + 3dgt) on 20A
AC Current	200µA/2mA/20mA/200mA/20A (50-500Hz)
Accuracy	± (1.2%rdg + 4dgt) on all ranges except ± (2%rdg + 4dgt) on 20A
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2000kΩ/20MΩ/200MΩ
Accuracy	± (0.8%rdg + 1dgt) on all ranges, except ± (1%rdg + 3dgt) on 200Ω ± (3%rdg + 3dgt) on 20MΩ ± (5%rdg + 10dgt) on 200MΩ
Sp. Function	Audible Continuity, Diode Check, hFE Test
Power	One 9V battery, Eveready type 216 or equivalent
Low Battery	"" is indicated
Battery Life	200 hours typical
Dimensions	170(H) X 80(W) X 38(D)mm
Weight	250gms approx.
Accessories	Supplied with pair of test leads, carrying case, battery, instruction manual and spare fuse