


Solar Module Analyzer (Photovoltaic I-V Curve Tester)










9009





Solar Panels




MECO Solar Module Analyzer Model 9009 is a portable analyzer used for testing, maintenance and finding efficiency of various parameters of solar panels and cells. Analyzer can be used to design Solar System to generate specific power. It can identify Solar Power System requirement, best angle of Solar Panel installation and Broken / Worn-out cells

Features

- I-V Curve Test for Solar Panel/Module/Cell
- Max. Solar Panel/Module/Cell Power (Pmax) search by Auto-Scan: 60V, 12A z(500W Capability)
- Best Resolution: 1mV, 1mA
- Manual Single Point I-V Test
- Max. Voltage (Vmaxp) at Pmax
- Max. Current (Imaxp) at Pmax
- Voltage at Open Circuit (Vopen)
- Current at Short Circuit (Ishort)
- I-V Curve with Cursor to Display each Data Point
- Efficiency (%) Calculation of Solar Panel
- Solar Panel Area Setting: $0.001 \text{ m}^2 \sim 9999 \text{ m}^2$
- Standard Light Source Setting: $10 \text{ W/m}^2 \sim 1000 \text{ W/m}^2$
- Communicate with PC via USB Cable
- AC Adaptor and Rechargeable Lithium Battery
- Memory Size: 100 Records
- Sampling Time of Data Logging: 0 ~ 99 min.
- Large LCD with Baclight

IV-Curve



General Specifications

| General Specifications | | | |
|-----------------------------|---|--|--|
| Battery Type | Rechargeable Lithium Battery, 3400mAh | | |
| Battery Life | 400 times of linear scan from 60V to 0V and 0A to 12A. | | |
| Data Logging Memory Size | 100 records | | |
| AC Adaptor | AC 110 ~ 240V Input, DC 15V / 1 ~ 3A Output | | |
| Dimension | 257 x 155 x 57mm (approx.) | | |
| Weight | 1160gms Including Battery (approx.) | | |
| Operation Environment | 0°C ~ 50°C, 85% RH | | |
| Temperature Coefficient | 0.1% of full scale / $^{\circ}$ C(<18 $^{\circ}$ C or >28 $^{\circ}$ C) | | |
| Storage Environment | -20°C ~ 60°C, 75% RH | | |
| Accessories | User Manual x 1, AC Adaptor x 1, Optical USB Cable x 1, Rechargeable Lithium Battery x 1, Software CD x 1, Software Manual x 1, Kelvin Clips (12A max) x 1 Set, 4 Wire to 2 Wire Connector (10A Max, 12A for 1minute) x 1 set, Carrying Bag x 1 | | |

Electrical Specifications (23°C ± 5°C, Four-Wire Measurement Maximum Power Limit is 500W)

DC Voltage Measurement

| Range | Resolution | Accuracy |
|----------|------------|---|
| 0 – 10V | 0.001V | $\pm 1\% \pm (1\% \text{ of Vopen } \pm 0.1\text{V})$ |
| 10 – 60V | 0.01V | \pm 1% \pm (1% of Vopen \pm 0.1V) |

Vopen: Open Circuit Voltage of Solar Cell or Module



Solar Module Analyzer (Photovoltaic I-V Curve Tester)

DC Current Measurement

| Range | Resolution | Accuracy |
|------------|------------|---|
| 0.01 – 10A | 1mA | $\pm 1\% \pm (1\% \text{ of Ishort } \pm 9\text{mA})$ |
| 10 – 12A | 10mA | $\pm 1\% \pm (1\% \text{ of Ishort } \pm 0.09\text{A})$ |

Ishort: Short Circuit Current of Solar Cell or Module

DC Current Simulation

| Range | Resolution | Accuracy |
|------------|------------|------------|
| 0.01 – 10A | 1mA | ±1% ±9mA |
| 10 - 12A | 10mA | ±1% ±0.09A |

Rear Panel Connections




PC Communication Window


User Interface & Data Acquisition Software

Solar Module Analyzer is supplied with user friendly software for Data Storing and Analysis. Users can store Data (.CSV/.TAB) that can be read in MS EXCEL and Print Waveform / Graph via Printer


Software Window



Cycle Scan



Print LCD



Applications

- Quality Control at Production Line, Warehouse or Site of Installation
- Identify Requirements of Solar Power System
- Maintenance of Solar Panels
- Verify the Best Installation Angles of Solar Panels
- Research and Development

4 Wire Measurement



Solar Panel Connections



Product Kit

