





Humidity & Temperature Meter

Humidity Measuring	
Functions	°C / °F / RH Selection, MAX / MIN,
	Auto Power Off
Range	0% ~ 100% RH
Accuracy	± 3%RH (25°C , 20 ~ 80% RH)
	± 3.5%RH (At Other Ranges)
Resolution	0.01%RH
Temperature Measuring	
Range	- 20°C ~ 80°C / - 4°F ~ 176°F
Accuracy	±0.5°C / ±0.9°F (25°C)
	±0.8°C / ±1.5°F (At Other Ranges)
Resolution	0.01°C / 0.01°F
Power	9V Battery
Dimensions	173 x 56 x 39mm (approx.)
Weight	139gms Including Battery (approx.)
Accessories	Carrying Case, Inst. Manual, 9V Battery (installed)

Air Flow Anemometer

Air Flow Measuring	
Functions	m / Sec, Ft / min, Knots, Km / h, MPH, CFM, MAX / MIN / HOLD, Auto Power Off
Range	1 ~ 25m/s
Accuracy	± (3% rdg ± 0.2m/s)
Resolution	0.01m/s
Temperature Measuring	
Range	0 ~ 50°C, 32 ~ 122°F
Accuracy	± 2°C / ± 4.0°F
Resolution	0.1°C/0.1°F
Power	9V Battery
Dimensions	202 x 56 x 39mm (approx.)
Weight	155gms Including Battery (approx.)
Accessories	Carrying Case, Inst. Manual, 9V Battery (installed)



Digital Sound Level Meter

Functions	MAX (MINI / HOLD, Auto Dourse Off
Functions	MAX / MIN / HOLD, Auto Power Off
Range	35dB ~ 130dB (31.5Hz ~ 8 Khz)
Accuracy	± 1.5dB (under reference conditions)
Resolution	0.1dB
Selection	-
Power	9V Battery
Dimensions	172 x 56 x 39 mm (approx.)
Weight	144gms Including Battery (approx.)
Accessories	Carrying Case, Inst. Manual, 9V Battery (installed)



Digital LUX Meter

Functions	MAX / MIN, Backlight, Auto Power Off
Range	0 ~ 200,000 lux 0 ~ 20,000 fc
Accuracy	±5% rdg+10 dgt (<10.000 lux/fc) ±10% rdg+10 dgt (>10.000 lux/fc)
Resolution	0.1lux or 0.1fc
Selection	lux / fc
Power	9V Battery
Dimensions	190 x 56 x 39mm (approx.)
Weight	135gms Including Battery (approx.)
Accessories	Carrying Case, Inst. Manual, 9V Battery (installed)