



सत्यमेव जयते

# TEST / CALIBRATION REPORT

## EMC / EMI Test Report for MECO Power Line Transducer

Testing as per BS EN 61326 (1998)



**ELECTRONICS REGIONAL TEST LABORATORY (WEST)**  
**MINISTRY OF COMMUNICATIONS & INFORMATION TECHNOLOGY, (STQC Dte.)**  
**Government of India**

Plot No. F 7 & 8, MIDC Area, Opp. SEEPZ,  
Andheri (E), Mumbai-400 093.  
Phone : (022) 832 5134, 830 1468, 830 1138 Fax : (022) 822 5713  
E-mail : ertlbom@bom4.vsnl.net.in

## MEMORANDUM

The Test/Calibration Report issued by **ERTL (W)** is a record of the measurements conducted on the products submitted to it for testing / calibration and the results thereof. Unless otherwise specified in the report, the results are applicable only to those products which have been tested / calibrated and do not apply to other products even though declared to be identical.

This Report, if reproduced for any purpose-commercial or otherwise would be reproduced in full. Reproduction of a part of the report or an abstract thereof must be specifically approved from the **ERTL (W)**.

## LIABILITY CLAUSE

1. **ERTL (W)** shall not be liable for any change in test / calibration data and performance specification on account of malfunctioning of the standard / instrument /equipment due to any damage caused to it after the report, in respect of it has been issued.
2. The report shall not be regarded in any way diminishing the normal contractual responsibilities / obligations between the customer and **ERTL (W)**.
3. The result reported in this report are valid only at the time of and under the stated conditions of the measurements.

<b>ELECTRONICS REGIONAL TEST LABORATORY (WEST)</b>	<b>REPORT NO.</b>		
<b>MINISTRY OF I.T. AND COMMUNICATIONS (STQC DTE)</b>	<b>ERTL(W)/ 2002EMI 149</b>		
<b>SUBJECT: EMC TEST ON POWER LINE TRANSDUCER</b>	<b>DATE</b>	<b>PAGE</b>	<b>OF</b>
	<b>14 AUG 2002</b>	<b>1</b>	<b>14</b>

1. SCOPE

1.1 Service Request No :ERTL(W)/2002 0994

1.1.1 Service Request finalised on : 23 MAY 2002


1.2 Requested by (Name and address of manufacturer) :MECO INSTRUMENTS PVT. LTD,  
301, BHARAT INDUSTRIAL ESTATE,  
T.J. ROAD, SEWREE,  
MUMBAI 400 015

1.3 Item No.	Description	Qty	Manufacturer and Type No.	Serial Nos
1.	POWER LINE TRANSDUCER	01	MECO/ WT34	---

1.4 Test specifications BS EN 61326 - 1998

1.5 Lab Ambient Temperature : (25 + 2) deg.C  
Humidity : (55 + 5) % RH

- 1.6 Test Equipment used :
1. EMI/003 : ESD Simulator (Schaffner, NSG 432)
  2. EMI/015 : Antenna Kit (EMCO, 1080) for R.E. test
  3. EMI/033 : EFT Simulator (EM-Test, EFT-800)
  4. EMI/034 : RS Chamber ( Keytek, G-Strip)
  5. EMI/036 : RF Signal Generator (HP, 8648 A) for C.S and R.S. tests
  6. EMI/037 : RF Amplifier (AR, 25A100) for R.S test
  7. CPU/064 : EMI System (HP, 8648 B ) for CE and RE tests
  8. EMI/038 : C D N (Keytek ) for C.S test
  9. EMI/044 : Immunity Test System(EM-Test, UCS 500 M6) for Surge test



ELECTRONICS REGIONAL TEST LABORATORY (WEST)	REPORT NO.		
MINISTRY OF I.T. AND COMMUNICATIONS (STQC DTE)	ERTL(W)/ 2002EMI 149		
SUBJECT: EMC TEST ON POWER LINE TRANSDUCER	DATE	PAGE	OF
	14 AUG 2002	2	14

## 2.0 EQUIPMENT UNDER TEST (EUT)

### 2.1 Description

WT 34 type Active and Reactive power transducers measure power in 1 Phase, 3 Phase three wire and 3 Phase four wire in balanced or unbalanced electrical systems and converts it to an industry standard O/P signal which is directly proportional to the measured I/P. These Transducers provide an O/P which is load independent and isolated from the I/P. These transducers can measure both Import and Export of Power. The O/P can be connected to Controllers, Data loggers, PLCs , Anaog/Digital indicators, Recorders for display , analysis and control. They are ideal for SCADA energy management, Telemetry,for Remote local as well as Central Monitoring stations.

### 2.2 Operating modes during emissions and immunity testing

Emission testing was carried out on 230VAC Auxiliary supply. During measurement, the three phase I/Ps were energized by 110 VAC supply and carrying a current of 1 A.

Immunity tests were carried out on both 230VAC Auxiliary and 110 VAC 3 phase supply. The 3 Phase supply was loaded with 1 A bulb load. The 20 mA current O/P was monitored.

### 2.3 Functional check for immunity tests


Variation in reading shall be less than  $\pm 0.5$  % of full span

### 2.4 Performance Criteria

**Criterion A** : During testing Normal performance within specification limits.

**Criterion B** : During testing, temporary degradation, or loss of function or performance which is self recoverable.

**Criterion C** : During testing, temporary degradation, or loss of function or performance which is recoverable by operator intervention or system reset.



<b>ELECTRONICS REGIONAL TEST LABORATORY (WEST)</b>	<b>REPORT NO.</b>		
<b>MINISTRY OF I.T. AND COMMUNICATIONS (STQC DTE)</b>	<b>ERTL(W)/ 2002EMI 149</b>		
<b>SUBJECT: EMC TEST ON POWER LINE TRANSDUCER</b>	<b>DATE</b>	<b>PAGE</b>	<b>OF</b>
	<b>14 AUG 2002</b>	<b>3</b>	<b>14</b>

### 3.1 CONDUCTED EMISSION

**Test Rationale :** To measure emissions of the EUT\* (referenced to Earth) on Power Mains and to compare them with specified limits to ascertain that the EUT will not disturb other equipment by generating such emissions above a certain limit

**a) Test Condition**


Set-up As per CISPR 22  
 Measurement Range 150 kHz – 30 MHz  
 Measurement On Auxiliary Supply  
 Line Voltage 230 V  
 Line Frequency 50 Hz  
 Length of mains 1 m

**EUT in normal operating condition as per Sr. No. 2.2**

**b) Receiver**

Bandwidth 9 KHz  
 Detectors Quasi – peak and Average  
 Configuration Conforming to CISPR 16

**c) Test procedure**



EUT supplied with required Auxiliary voltage through an LISN. Emission of the EUT were measured with a Spectrum Analyser.

**d) Requirements**

EUT emissions shall be below following Class 'B' limits

Freq. (MHz)	Limits (dBuV)	
	Quasi-Peak	Average
0.15-0.5	66-56	56-46
0.5-5	56	46
5-30	60	50


**e) Observations**

Pl. see Graph at page 14 of 14

**f) Results**

Complies with Class 'B' Limits

\* EUT : Equipment Under Test



<b>ELECTRONICS REGIONAL TEST LABORATORY (WEST)</b>	<b>REPORT NO.</b>		
<b>MINISTRY OF I.T. AND COMMUNICATIONS (STQC DTE)</b>	<b>ERTL(W)/ 2002EMI 149</b>		
<b>SUBJECT: EMC TEST ON POWER LINE TRANSDUCER</b>	<b>DATE</b>	<b>PAGE</b>	<b>OF</b>
	<b>14 AUG 2002</b>	<b>4</b>	<b>14</b>

### 3.2 RADIATED EMISSION

#### Test Rationale :

To measure emissions of the EUT radiated into space and to compare them with specified limits to ascertain that the EUT will not disturb other equipment by generating such emissions above a certain limit.

**a) Test Condition :**

Set-up As per CISPR 22  
Frequency Range 30 MHz – 1000MHz  
**EUT in normal operating condition as per Sr. No. 2.2**

**b) Reciever :**

Bandwidth 120 KHz  
Detectors QP  
Antenna Bi-Conical (For 30 – 200 MHz)  
Log-Periodic (For 200 – 1000 MHz)  
Configuration Conforming to CISPR 16

**c) Test procedure**

- Emission measurements were carried out in an Open Area Test Site (OATS)
- Ambient measurements carried out first with EUT "off" and peaks noted
- EUT was switched "ON" and Emission peaks noted.
- Antenna height and position were changed to maximize Emissions.
- A table of Emission and corresponding Ambients was then drawn up.
- "Ambient" and "Emission" peaks were compared. Peaks with a difference of less than 5 dB were discarded.

**d) Requirements**

EUT emissions shall be below following limits


Freq. (MHz)	Limits (dBuV/m)
30-230	40.45
230-1000	47.45

**e) Observations**

Maximum Emissions were obtained from front portion of EUT in Horizontal Polarisation and Antenna ht of 1 m  
Pl. see Table at page of for details

**f) Results**

**Complies with Class 'B' limits**




ELECTRONICS REGIONAL TEST LABORATORY (WEST)	REPORT NO.		
MINISTRY OF I.T. AND COMMUNICATIONS (STQC DTE)	ERTL(W)/ 2002EMI 149		
SUBJECT: EMC TEST ON POWER LINE TRANSDUCER	DATE	PAGE	OF
	14 AUG 2002	5	14

### 3.3 RADIATED SUSCEPTIBILITY (RS) (Amplitude Modulated)

#### Test Rationale

To check immunity characteristics of the EUT in the presence of radiated fields generated by intentional emitters like Radio /TV transmitters, wireless equipment and the like by illuminating the EUT by such frequency

- a **Test Condition :**
- |                 |                      |
|-----------------|----------------------|
| Set-up          | As per IEC 61000-4-3 |
| Frequency Range | 80 MHz – 1000MHz     |
| Modulation      | 80 % AM @ 1 kHz      |
| Amplitude       | 10V/m                |
- Simulation** Using G-Strip RF immunity chamber  
EUT in normal operating condition as per Sr. No. 2.2
- c **Test procedure**  
EUT was illuminated with the required field strength inside the test chamber, and operation was monitored.
- d **Requirements**  
Operation of the EUT shall be normal as per Sr. No. 2.3 during and after the test.  
Performance Criterion : 'A'
- e **Observations**  
Operation of the EUT was normal as per Sr. No. 2.3 during and after the test. No variation in O/P current could be observed
- f **Results**  
Complies with Criterion 'A'



<b>ELECTRONICS REGIONAL TEST LABORATORY (WEST)</b>	<b>REPORT NO.</b>		
<b>MINISTRY OF I.T. AND COMMUNICATIONS (STQC DTE)</b>	<b>ERTL(W)/ 2002EMI 149</b>		
<b>SUBJECT: EMC TEST ON POWER LINE TRANSDUCER</b>	<b>DATE</b>	<b>PAGE</b>	<b>OF</b>
	<b>14 AUG 2002</b>	<b>6</b>	<b>14</b>

### 3.4 ELECTROSTATIC DISCHARGE (ESD)

#### Test Rationale :

To check immunity characteristics of the EUT against Discharge of Static Electricity that may occur when a charged operator touches the EUT.

#### a Test Condition :

**Set-up** As per IEC 61000-4-2

**Mode of simulation:** Contact Discharge on conductive surfaces  
Air Discharge on non- conductive surfaces

**Test Voltage:** Contact Discharge: 4kV  
Air Discharge: 8kV

**No. of Discharges** 10

**Polarity** Positive and Negative

**Points of Discharge** **Contact Discharge**  
Maintenance screws  
**Air Discharge :**  
EUT body

**Simulation** Using ESD Gun

**EUT in normal operating condition as per Sr. No. 2.2**

#### c Test procedure :

- EUT initially subjected to indirect discharge on VCP and HCP.
- EUT was then screened in continuous discharge mode.
- At susceptible points, ten single discharges were applied.

#### d Requirement :

Operation of the EUT shall be normal as per Sr. No. 2.3 after the test.  
Performance Criterion : 'B'

#### e Observations :

Operation of the EUT was normal as per Sr. No. 2.3 during and after the test. No variation in O/P current could be observed

#### f Results :

Air Discharge : Complies with Criterion 'A'  
Contact Discharge : Complies with Criterion 'A'





<b>ELECTRONICS REGIONAL TEST LABORATORY (WEST)</b>	<b>REPORT NO.</b>		
<b>MINISTRY OF I.T. AND COMMUNICATIONS (STQC DTE)</b>	<b>ERTL(W)/ 2002EMI 149</b>		
<b>SUBJECT: EMC TEST ON POWER LINE TRANSDUCER</b>	<b>DATE</b>	<b>PAGE</b>	<b>OF</b>
	<b>14 AUG 2002</b>	<b>7</b>	<b>14</b>

**3.5 ELECTRICAL FAST TRANSIENTS (EFT)**

**Test Rationale :**


To check immunity characteristics of the EUT against transients generated by inductive load switching, Relay contact bouncing, switching of high voltage switchgear and the like

**a Test Condition :**

- Set-up** As per IEC 61000-4-4
- Pulse** 5/50 nSec
- Modes** Common and Differential
- Pulse Amplitude** 2 kV
- Pulse Rep. Rate** 5 kHz
- Polarity** Positive and Negative
- Duration of test in each mode** 60 s
- Simulation** On 230 VAC Auxiliary and 110V Three Phase I/P by Direct Injection

**EUT in normal operating condition as per Sr. No. 2.2.**

**c Test procedure :**



- Transients generated by the generator were coupled to the 230 VAC Auxiliary Supply through a coupling N/W
- The level was stepped up from minimum to the specified severity in steps of 0.5 kV to determine threshold of failure.
- The test was repeated on 110 VAC Three Phase I/P lines

**d Requirements :**


Operation of the EUT shall be normal as per Sr. No. 2.3 after the test.  
Performance Criterion : 'B'

**e Observations :**

Simulation on Auxiliary Supply : Operation of the EUT was normal as per Sr. No. 2.3 during and after the test.. No variation in O/P current could be observed  
Simulation on Three phase I/P: Operation of the EUT was normal as per Sr. No. 2.3 during and after the test. No variation in O/P current could be observed

**f Results :**

Auxiliary Supply : Complies with Criterion 'A'  
Three phase I/P: Complies with Criterion 'A'



<b>ELECTRONICS REGIONAL TEST LABORATORY (WEST)</b>	<b>REPORT NO.</b>		
<b>MINISTRY OF I.T. AND COMMUNICATIONS (STQC DTE)</b>	<b>ERTL(W)/ 2002EMI 149</b>		
<b>SUBJECT: EMC TEST ON POWER LINE TRANSDUCER</b>	<b>DATE</b>	<b>PAGE</b>	<b>OF</b>
	<b>14 AUG 2002</b>	<b>8</b>	<b>14</b>

### 3.6 CONDUCTED RF SUSCEPTIBILITY


#### Test Rationale :

To study immunity characteristics of the EUT when subjected to continuous conducted Noise.

#### a Test Condition :

Set-up As per IEC 61000-4-6  
 Frequency 150 kHz – 100MHz  
 Modulation 80 % AM @ 1 kHz  
 Amplitude 3V  
 Simulation On 230 VAC Auxiliary and 110V Three Phase I/P Using CDN  
**EUT in normal operating condition as per Sr. No. 2.2**

#### c Test procedure :



- The required simulation signal was generated by the Signal Generator and the Amplifier
- It was then coupled onto 230 VAC Auxiliary supply using CDN and operation of EUT was monitored
- The test was repeated on 110VAC Three Phase I/P lines.

#### d Requirements :


Operation of the EUT shall be normal as per Sr. No. 2.3 after the test.  
 Performance Criterion : 'A'

#### e Observations :

Simulation on Auxiliary Supply : Operation of the EUT was normal as per Sr. No. 2.3 during and after the test.. No variation in O/P current could be observed  
 Simulation on Three phase I/P: Operation of the EUT was normal as per Sr. No. 2.3 during and after the test. No variation in O/P current could be observed

#### f Results :

Auxiliary Supply : Complies with Criterion 'A'  
 Three phase I/P: Complies with Criterion 'A'



<b>ELECTRONICS REGIONAL TEST LABORATORY (WEST)</b>	<b>REPORT NO.</b>		
<b>MINISTRY OF I.T. AND COMMUNICATIONS (STQC DTE)</b>	<b>ERTL(W)/ 2002EMI 149</b>		
<b>SUBJECT: EMC TEST ON POWER LINE TRANSDUCER</b>	<b>DATE</b>	<b>PAGE</b>	<b>OF</b>
	<b>14 AUG 2002</b>	<b>9</b>	<b>14</b>

### 3.7 SURGE


#### Test Rationale :

To check immunity characteristics of the EUT against Surges generated because of Capacitive Bank Switching, Faults, Lightning and the like.

#### a Test Condition :

**Set-up** As per IEC 61000-4-5  
**Pulse** 1.2 / 50 uS  
**Modes** Common (Line to Ground ) and Differential (Line to Line)  
**Pulse Amplitude** Common Mode : 2 kV  
Differential Mode : 1kV  
**Polarity** Positive and Negative  
**No. of transients** Five in each mode  
**Simulation** On 230 VAC Auxiliary and 110V Three Phase I/P by Direct Injection  
**EUT in normal operating condition as per Sr. No. 2.2**

#### c Test procedure :



- Surges generated by the generator were coupled to the mains and I/O through respective coupling N/Ws.
- The level was stepped up from minimum to the specified severity in steps of 0.5 kV to determine threshold of failure.
- The test was repeated on 110 VAC Three Phase I/P lines

#### d Requirements :

Operation of the EUT shall be normal as per Sr. No. 2.3 after the test.  
Performance Criterion : 'B'

#### e Observations :

Simulation on Auxiliary Supply : Operation of the EUT was normal as per Sr. No. 2.3 during and after the test.. No variation in O/P current could be observed  
Simulation on Three phase I/P: Operation of the EUT was normal as per Sr. No. 2.3 during and after the test. No variation in O/P current could be observed

#### f Results :

Auxiliary Supply : Complies with Criterion 'A'.  
Three phase I/P : Complies with Criterion 'A'.



<b>ELECTRONICS REGIONAL TEST LABORATORY (WEST)</b>	<b>REPORT NO.</b>		
<b>MINISTRY OF I.T. AND COMMUNICATIONS (STQC DTE)</b>	<b>ERTL(W)/ 2002EMI 149</b>		
<b>SUBJECT: EMC TEST ON POWER LINE TRANSDUCER</b>	<b>DATE</b>	<b>PAGE</b>	<b>OF</b>
		<b>10</b>	<b>14</b>

**14 AUG 2002**

### 3.8 VOLTAGE DIPS AND INTERRUPTIONS

#### Test Rationale :

To study performance of the EUT when subjected to voltage dips and interruptions

**a Test Condition :**

**Set-up** As per IEC 61000-4-11  
**Line Voltage** 230 VAC  
**Line Frequency** 50 Hz  
**Reduction** 100%  
**Duration** 10 mSec (0.5 cycle)  
**Simulation** On 230 VAC Auxiliary supply.  
**EUT in normal operating condition as per Sr. No. 2.2**

**c Test procedure :**

The above conditions were simulated using dedicated test system and operation of the EUT was monitored

**d Requirements :**


Operation of the EUT shall be normal as per Sr. No. 2.3 after the test.  
Performance Criterion : 'C'

**e Observations :**

Operation of the EUT was normal as per Sr. No. 2.3 during and after the test. No variation in O/P current could be observed.

**f Results :**

Complies with Criterion 'A'




ELECTRONICS REGIONAL TEST LABORATORY (WEST)	REPORT NO.		
MINISTRY OF I.T. AND COMMUNICATIONS (STQC DTE)	ERTL(W)/ 2003EMI 149		
SUBJECT: EMC TEST ON POWER LINE TRANSDUCER	DATE	PAGE	OF
	13 MAR 2003	11	14

**4.2 EMC modifications incorporated**

**Conducted RF Susceptibility**

- A Power Line Filter was introduced in the power mains. It was mounted close to the mains entry point to reduce long length of unfiltered mains.




Released By

This is an amended version of page 11 Of 14 of report No ERTL(W)/2002EMI149

Amendment Issued By

*(Handwritten signature)*

Amendment Released By




ELECTRONICS REGIONAL TEST LABORATORY (WEST) MINISTRY OF I.T. AND COMMUNICATIONS (STQC DTE)	REPORT NO. ERTL(W)/ 2002EMI 149		
SUBJECT: EMC TEST ON POWER LINE TRANSDUCER	DATE <b>14 AUG 2002</b>	PAGE 12	OF 14

3.0 General Remarks :


\_\_\_\_\_

REPORT APPROVED BY



HEAD (EMI/PCT)

REPORT RELEASED BY





OIC (S)



ELECTRONICS REGIONAL TEST LABORATORY (WEST)	REPORT NO.		
MINISTRY OF I.T. AND COMMUNICATIONS (STQC DTE)	ERTL(W)/ 2002EMI 149		
SUBJECT: EMC TEST ON POWER LINE TRANSDUCER	DATE 14 AUG 2002	PAGE 13	OF 14

**Radiated Emission Test Results**


Sr.	Frequency(MHz)	Emissions (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Results
1.	37.4	26.85	40.45	Pass
2.	50.2	23.45	40.45	Pass
3.	74.7	20.3	40.45	Pass
4.	81.3	17.4	40.45	Pass
5.	84.7	20.51	40.45	Pass
6.	147.1	26.85	40.45	Pass
7.	181.2	30.75	40.45	Pass
8.	205.1	30.3	40.45	Pass



14 AUG 2002

8 JUL 2002 02:58:57

ERTL (w) MUMBAI  
EMISSION LEVEL [ dBuV ]



EN 61326 CLASS B CONDUCTED  
ACTIVE POWER TRANSDUCER  
JC. NO. 2002EMI149  
MODEL WT33 SR. NO. 021771  
PAGE 1 OF 1



FREQUENCY [ MHz ]

30

1

.15



## OUR ACCREDITATION STATUS

ERTL (W) set up under the STQC Directorate, Ministry of Communications & Information Technology, Govt. of India has been accredited under number of national / international systems as follows :

SYSTEM	AREA	STATUS
<b>IECQ</b> (International Electro-technical Commission on Quality Assessment System for Electronic Components)	<b>Component Testing</b> <ul style="list-style-type: none"> <li>● Resistors (Fixed)</li> <li>● Capacitors (Fixed)</li> </ul>	Accredited as ITL (Independent Test Laboratory)
<b>NABL (C), India</b> National Accredital Board for Test & Calibration laboratories (Calibration System)	<b>Calibration</b> <ul style="list-style-type: none"> <li>● Electro-technical discipline</li> <li>● Thermal discipline</li> <li>● Mechanical discipline</li> </ul>	Accredited Calibration Laboratory
<b>NABL(T), India</b> National Accredital Board for Test & Calibration laboratories (Testing System)	Electronic & Electrical Testing	Accredited Test Laboratory
<b>IECEE-CE-Scheme</b>	<ul style="list-style-type: none"> <li>● Mains Operated Electronic Consumer Products</li> </ul>	Approved as a CB test Laboratory
<b>Other recognition</b>		Recognised by CSPO of State Govt., DOT, Naval Docyard, LCSO etc.