



9A06



801AUTO

Auto / Manual, 3½ Digit, 2000 Counts LCD, APO & Temperature		Auto / Manual, 3¾ Digit, 4000 Counts LCD, APO, Capacitance, Frequency, Duty Cycle & Temperature		Accessories	
Ranges		Ranges		One Pair of Test Leads, Battery (installed), K Type Thermocouple (upto 260°C), Inst. Manual & Carrying Case	
DC Voltage	200mV/2/20/200/1000V	DC Voltage	400mV/4/40/400/1000V		
Accuracy	± [0.5%rdg + 4dgt] on 200mV & 2V, ± [0.7%rdg + 4dgt] on 20V & 200V, ± [1%rdg + 4dgt] on 1000V	Accuracy	± [0.5% rdg + 4 dgt] on 400mV/4V ± [0.7% rdg + 4 dgt] on 40/ 400V ± [1.0% rdg + 4 dgt] on 1000V	Accessories	
AC Voltage	200mV/2/20/200/750V (200mV Manual only)	AC Voltage	4/40/400/750V	K Type Bead Probe (upto 260°C) Model : TPK-B	
Accuracy	± [1.0%rdg + 8dgt] on all ranges except ± [1.5%rdg + 8dgt] on 750V	Accuracy	± [1.0% rdg + 5 dgt] on all ranges except ± [1.5% rdg + 8 dgt] on 750V	K Type Stick Probe (upto 500°C) Model : TP-02	
DC Current	200/2000µA/20/200mA/ 2/10A	DC Current	400/4000µA/40/400mA/ 4/20A	Pair of Test Leads suitable for DMM/DTT Model : TL-DMM/DTT	
Accuracy	± [1.5%rdg + 4dgt]	Accuracy	± [1.5% rdg + 4 dgt]	Pair of Test Leads suitable for Insulation Tester Model : TL-IT	
AC Current	200/2000µA/20/200mA/ 2/10A	AC Current	400/4000µA/40/400mA/ 4/20A		
Accuracy	± [2.2%rdg + 4dgt]	Accuracy	± [2.2% rdg + 4 dgt]		
Resistance	200Ω/2/20/200kΩ/2/20MΩ	Resistance	400Ω/4/40/400kΩ/4/40MΩ		
Accuracy	± [0.7%ordg + 4dgt] on all ranges except ± [1.2%rdg + 4dgt] on 2MΩ ± [2.5%rdg + 4dgt] on 20MΩ	Accuracy	± [0.7% rdg + 4 dgt] on all ranges except ± [1.2% rdg + 4 dgt] on 4MΩ ± [2.5% rdg + 4 dgt] on 40MΩ		
Temperature	-20°C-1300°C / -4°F-1999°F	Capacitance	40/400nF/4/40/100µF		
Accuracy	± [2%rdg + 4dgt]	Accuracy	± [5.0% rdg + 10 dgt]		
Measuring Category	CAT II	Frequency	9.999Hz ~9.999MHz		
Sp. Function	Diode Test, Audible Continuity, Data Hold	Accuracy	± [0.5% rdg + 2 dgt]		
Power	Two 1.5V 'AA' Battery	Duty Cycle	0.1% ~ 99.9%		
Low Battery	"E" Indicated	Accuracy	± [0.5% rdg + 2 dgt]		
Battery Life	200 hours typical	Temperature	-20°C-1300°C		
Dimensions	161 x 86 x 43 mm (approx.)	Accuracy	± [2% rdg + 4 dgt]		
Weight	250gms Including Battery (approx.)	Measuring Category	CAT II		
Accessories	One Pair of Test Leads, Battery (installed), K Type Thermocouple (upto 260°C), Inst. Manual & Carrying Case	Sp. Function	Diode Test, Audible Continuity, Data Hold		
		Power	Two 1.5V 'AA' Battery		
		Low Battery	"E" is indicated		
		Battery Life	200 hours typical		
		Dimensions	161 x 86 x 43 mm (approx.)		
		Weight	250gms Including Battery (approx.)		