



72-AUTO BL



72T-AUTO BL



2520THz-AUTO BL

600A AC TRMS	600A AC TRMS	1000A AC TRMS
Auto Ranging, 3% Digit, 4000 Counts, Data Hold, Rel.Test, Backlight, Torchlight, NCV (LED, Buzzer & EF Strength), APO	Auto Ranging, 3% Digit, 4000 Counts, Temperature, Capacitance, Data Hold, Rel.Test, Backlight, Torchlight, NCV (LED, Buzzer & EF Strength), APO	Auto / Manual, 3% Digit, 6000 Counts, Temperature, Capcintance, Data Hold, Backlight, Hz/ Duty, Torchlight, NCV (LED, Buzzer & EF Strength), APO
Ranges	Ranges	Ranges
AC Current ^{TRMS} 40A, 400A, 600A (Auto Ranging)	AC Current ^{TRMS} 40A, 400A, 600A (Auto Ranging)	AC Current ^{TRMS} 60A, 600A, 1000A
Accuracy ±(2.5%rdg+5dgt)	Accuracy ±(2.5%rdg+5dgt)	Accuracy ±(2.5%rdg+5dgt)
AC Response 40Hz ~ 1KHz	AC Response 40Hz ~ 1KHz	AC Response 40Hz ~ 1KHz
Overload 600A AC max. for 1 min.	Overload 600A AC max. for 1 min.	Overload 1000A AC max. for 1 min.
DC Voltage 400mV, 4V, 40V, 400V, 600V (Auto Ranging)	DC Voltage 400mV, 4V, 40V, 400V, 600V (Auto Ranging)	DC Voltage 600mV, 6V, 60V, 600V, 1000V
Accuracy ±(0.8%rdg+3dgt)	Accuracy ±(0.8%rdg+3dgt)	Accuracy ±(0.8%rdg+3dgt)
AC Voltage ^{TRMS} 4V, 40V, 400V, 600V (Auto Ranging)	AC Voltage ^{TRMS} 4V, 40V, 400V, 600V (Auto Ranging)	AC Voltage ^{TRMS} 6V, 60V, 600V, 750V
Accuracy ±(1.2%rdg+3dgt)	Accuracy ±(1.2%rdg+3dgt)	Accuracy ±(1.2%rdg+3dgt)
AC Response 40Hz ~ 1KHz	AC Response 40Hz ~ 1KHz	AC Response 40Hz ~ 1KHz
Resistance 400Ω, 4kΩ, 40KΩ, 400kΩ, 4MΩ, 40MΩ (Auto Ranging)	Resistance 400Ω, 4kΩ, 40KΩ, 400kΩ, 4MΩ, 40MΩ (Auto Ranging)	Resistance 600Ω, 6kΩ, 60KΩ, 600kΩ, 6MΩ, 60MΩ
Accuracy ±(1.2%rdg+3dgt)	Accuracy ±(1.2%rdg+3dgt)	Accuracy ±(1.2%rdg+3dgt)
Frequency 4Hz ~ 1MHz (Auto Ranging)	Frequency 4Hz ~ 1MHz (Auto Ranging)	Frequency 10Hz ~ 10MHz (Auto Ranging)
Accuracy ±(0.5%rdg+2dgt)	Accuracy ±(0.5%rdg+2dgt)	Accuracy ±(0.5%rdg+2dgt)
Safety Standard CAT II 600V	Temperature -20°C to 750°C / -4°F to 1382°F	Duty Cycle 0.1% ~ 99.9%
Audible Continuity 40Ω (approx.)	Accuracy ±(3%rdg+5dgt)	Accuracy ±(0.5%rdg+2dgt)
Diode Test 1.0 ±0.6mA (approx.)	Safety Standard CAT II 600V	Temperature -20°C to 750°C / -4°F to 1382°F
Power Two 1.5V 'AAA' Battery	Audible Continuity 40Ω (approx.)	Accuracy ±(3%rdg+5dgt)
Low Battery "⚡" is indicated	Diode Test 1.0 ±0.6mA (approx.)	Safety Standard CAT III 600V
Battery Life 200 Hours Typical	Power Two 1.5V 'AAA' Battery	Audible Continuity 30Ω (approx.)
Dimension 185 x 65 x 28 mm (approx.)	Low Battery "⚡" is indicated	Diode Test 1.0 ±0.6mA (approx.)
Weight 170gms Including Battery (approx.)	Battery Life 200 Hours Typical	Power Two 1.5V 'AA' Battery
Jaw Opening Cable Dia. 25mm (max.)	Battery Life 200 Hours Typical	Low Battery "⚡" is indicated
Accessories One Pair of Test Leads, Instruction Manual, Carrying Case, Battery (installed)	Dimension 185 x 65 x 28 mm (approx.)	Battery Life 200 Hours Typical
	Weight 170gms Including Battery (approx.)	Dimension 245 x 95 x 35 mm (approx.)
	Jaw Opening Cable Dia. 25mm (max.)	Weight 309gms Including Battery (approx.)
	Accessories One Pair of Test Leads, Instruction Manual, Carrying Case, Battery (installed), K Type Thermocouple (upto 260°C)	Jaw Opening Cable Dia. 52mm (max.)
		Accessories One Pair of Test Leads, Instruction Manual, Carrying Case, Battery (installed), K Type Thermocouple (upto 260°C)