



1008P+



1080P+

1000A AC TRMS	
Auto / Manual, 3% Digit, 6000 Counts LCD with Backlight, Torchlight, Capacitance, Frequency, Duty Cycle, Temperature, NCV (LED, Buzzer & EF Strength), Live Test & APO	
Ranges	
AC Current	60 / 600 / 1000A
Accuracy	± (2.5% rdg + 10dgt)
AC Response	40 Hz ~ 400Hz
Overload	1000A AC Max. for 1min.
DC Voltage	6/60/600/1000V
Accuracy	± (0.8%rdg + 3dgt) on 6V ± (1.0%rdg + 5dgt)
AC Voltage	6/60/600/1000V
Accuracy	± (1.2%rdg + 6dgt) on 6V ± (1.2%rdg + 8dgt)
AC Response	40Hz ~ 400Hz
Resistance	600Ω/6/60/600kΩ/6/60MΩ
Accuracy	± (1.5%rdg + 5dgt) ± (3.0%rdg + 5dgt) on 60MΩ
Capacitance	6nF, 60nF, 600nF, 6μF, 60μF, 600μF, 6mF, 60mF
Accuracy	± (5.0% rdg + 8dgt)
Frequency	9.999Hz ~ 9.999MHz
Accuracy	± (2.0% rdg + 3dgt)
Duty Cycle	0.1% ~ 99.9%
Accuracy	± (1.0% rdg + 3dgt)
Temperature	-40°C ~ 1000°C/-40°F ~ 1832°F
Accuracy	± (5°C)/± (5°F) -40°C ~ 0°C/-40°F ~ 0°F ± (2% rdg + 5°C)/± (2% rdg + 9°F) 0°C ~ 600°C/0°F ~ 600°F ± (2.5% rdg + 3°C)/± (2.5% rdg + 9°F) 600°C ~ 1000°C/600°F ~ 1832°F
Category	CAT III 1000V
Sp. Function	Diode Test, Audible Continuity, Data Hold
Power	Two 1.5V 'AAA' Battery
Low Battery	"" is indicated
Battery Life	200 hours typical
Dimension	241 x 89 x 43mm (approx.)
Weight	281gms Including Battery
Jaw Opening	Cable Dia. 38mm (max.)
Accessories	One Pair of Test Leads, Battery (installed), K Type Thermocouple (upto 230°C), Instruction Manual & Carrying Case

1000A DC / AC TRMS	
Auto / Manual, 3% Digit, 6000 Counts LCD with Backlight, Torchlight, Capacitance, Frequency, Duty Cycle, Temperature, NCV (LED, Buzzer & EF Strength), Live Test & APO	
Ranges	
DC Current	60 / 600 / 1000A
Accuracy	± (2.5% rdg + 10dgt)
Overload	1000A DC Max. for 1min.
AC Current	60 / 600 / 1000A
Accuracy	± (2.5% rdg + 10dgt)
AC Response	40 Hz ~ 400Hz
Overload	1000A AC Max. for 1min.
DC Voltage	6/60/600/1000V
Accuracy	± (0.8%rdg + 3dgt) on 6V ± (1.0%rdg + 5dgt)
AC Voltage	6/60/600/1000V
Accuracy	± (1.2%rdg + 6dgt) on 6V ± (1.2%rdg + 8dgt)
AC Response	40Hz ~ 400Hz
Resistance	600Ω/6/60/600kΩ/6/60MΩ
Accuracy	± (1.5%rdg + 5dgt) ± (3.0%rdg + 5dgt) on 60MΩ
Capacitance	6nF, 60nF, 600nF, 6μF, 60μF, 600μF, 6mF, 60mF
Accuracy	± (5.0% rdg + 8dgt)
Frequency	9.999Hz ~ 9.999MHz
Accuracy	± (2.0% rdg + 3dgt)
Duty Cycle	0.1% ~ 99.9%
Accuracy	± (1.0% rdg + 3dgt)
Temperature	-40°C ~ 1000°C/-40°F ~ 1832°F
Accuracy	± (5°C)/± (5°F) -40°C ~ 0°C/-40°F ~ 0°F ± (2% rdg + 5°C)/± (2% rdg + 9°F) 0°C ~ 600°C/0°F ~ 600°F ± (2.5% rdg + 3°C)/± (2.5% rdg + 9°F) 600°C ~ 1000°C/600°F ~ 1832°F
Category	CAT III 1000V
Sp. Function	Diode Test, Audible Continuity, Data Hold
Power	Two 1.5V 'AAA' Battery
Low Battery	"" is indicated
Battery Life	200 hours typical
Dimension	241 x 89 x 43mm (approx.)
Weight	310gms Including Battery
Jaw Opening	Cable Dia. 38mm (max.)

Accessories	One Pair of Test Leads, Battery (installed), K Type Thermocouple (upto 230°C), Instruction Manual & Carrying Case
--------------------	---

Accessories	
K Type Bead Probe (upto 260°C) Model : TPK-B	
K Type Stick Probe (upto 500°C) Model : TP-02	
Pair of Test Leads suitable for DMM/DTT Model : TL-DMM/DTT	
Pair of Test Leads suitable for Insulation Tester Model : TL-IT	