



135P+



LCR99



1) Above 60.00V DC



2) Above 36.00V AC

Red Backlight for High Voltage Alert

TRMS, Auto / Manual, 4 Digits 9999 Counts Digital Dual Display LCD with Backlight, APO, Resistance, Capacitance, Frequency, Duty Cycle, ΔREL, Data Hold, Max/Min, Peak, Red & Green Light Indication for Input Terminal Selection, NCV, Torchlight & Bargraph

DC Voltage	99.99 / 999.9mV / 9.999 / 99.99 / 999.9V
Accuracy	± (0.5% rdg + 5 dgt) on all ranges except ± (0.8% rdg + 5 dgt) on 999.9V
AC Voltage	99.99 / 999.9mV / 9.999 / 99.99 / 750.0V
Accuracy	± (1.0% rdg + 4 dgt) on all ranges except ± (1.2% rdg + 4 dgt) on 750.0V
AC Response	10Hz ~ 1KHz
DC Current	999.9μA / 999.9mA / 9.999A
Accuracy	± (1.2% rdg + 5 dgt) on 999.9μA, 999.9mA ± (2.0% rdg + 5 dgt) on 9.999A
AC Current	999.9μA / 999.9mA / 9.999A
Accuracy	± (1.5% rdg + 5 dgt) on 999.9μA, 999.9mA ± (2.0% rdg + 5 dgt) on 9.999A
AC Response	40Hz ~ 1KHz
Resistance	999.9Ω / 9.999 / 99.99 / 999.9KΩ / 9.999 / 99.99MΩ
Accuracy	± (0.8% rdg + 5 dgt) on all ranges except ± (1.2% rdg + 5 dgt) on 99.99MΩ
Capacitance	9.999 / 99.99 / 999.9nF / 9.999 / 99.99 / 999.9μF / 9.999 / 99.99mF
Accuracy	± (4.0% rdg + 5 dgt) on all ranges except ± (5.0% rdg + 5 dgt) on 9.999 / 99.99mF
Frequency	9.99Hz ~ 9.99MHz
Accuracy	± (1.5% rdg + 5 dgt)

TRMS, Auto / Manual, 4 Digits 9999 Counts Digital Dual Display LCD with Auto Backlight, APO, Resistance, Capacitance, Inductance, Frequency, Duty Cycle, ΔREL, Data Hold, Max/Min, Peak, Red & Green Light Indication for Input Terminal Selection, NCV, Torchlight & Bargraph

DC Voltage	99.99 / 999.9mV / 9.999 / 99.99 / 999.9V
Accuracy	± (0.5% rdg + 5 dgt) on all ranges except ± (0.8% rdg + 5 dgt) on 999.9V
AC Voltage	99.99 / 999.9mV / 9.999 / 99.99 / 750.0V
Accuracy	± (1.0% rdg + 4 dgt) on all ranges except ± (1.2% rdg + 4 dgt) on 750.0V
AC Response	10Hz ~ 1KHz
DC Current	999.9 / 999.9mA / 9.999A
Accuracy	± (1.2% rdg + 5 dgt)

Duty Cycle	0.1% ~ 99.9%
Accuracy	± (1.5% rdg + 5 dgt)
Temperature	-55°C ~ 1000°C / -67°F ~ 1832°F
Accuracy	± (1.0% rdg + 3 dgt)
Measuring Category	CAT II 1000V, CAT III 600V
SP Function	Diode Test, Audible Continuity
Power	Three 1.5V 'AAA' Battery
Low Battery	'E' is indicated
Battery Life	200 hours typical
Dimensions	187 x 95 x 55 mm (approx.)
Weight	350gms Including Battery (approx.)
Accessories	One Pair of Test Leads, Holster, Battery (installed), Instruction Manual, Carrying Case & K Type Thermocouple (upto 260°C)

AC Current	99.99 / 999.9mA / 9.999A
Accuracy	± (1.5% rdg + 5 dgt) on 99.99 / 999.9mA ± (2.0% rdg + 5 dgt) on 9.999A
AC Response	40Hz ~ 1KHz
Resistance	999.9Ω / 9.999 / 99.99 / 999.9KΩ / 9.999 / 99.99MΩ
Accuracy	± (0.8% rdg + 5 dgt) on all ranges except ± (1.2% rdg + 5 dgt) on 99.99MΩ
Capacitance	9.999 / 99.99 / 999.9nF / 9.999 / 99.99 / 999.9μF / 9.999 / 99.99mF
Accuracy	± (4.0% rdg + 5 dgt) on all ranges except ± (5.0% rdg + 5 dgt) on 9.999 / 99.99mF
Inductance	9.999mH ~ 99.99H
Accuracy	± (4.0% rdg + 5 dgt)
Frequency	9.99Hz ~ 9.99MHz
Accuracy	± (1.5% rdg + 5 dgt)
Duty Cycle	0.1% ~ 99.9%
Accuracy	± (1.5% rdg + 5 dgt)
Temperature	-55°C ~ 1000°C / -67°F ~ 1832°F
Accuracy	± (1.0% rdg + 3 dgt)
Measuring Category	CAT II 1000V, CAT III 600V
SP Function	Diode Test, Audible Continuity
Power	Three 1.5V 'AAA' Battery
Low Battery	'E' is indicated
Battery Life	200 hours typical
Dimensions	187 x 95 x 55 mm (approx.)
Weight	350gms Including Battery (approx.)
Accessories	One Pair of Test Leads, Holster, Battery (installed), Instruction Manual, Carrying Case & K Type Thermocouple (upto 260°C)