




DC Current Adaptor

6390



Software Window

Features

- Right Device to know the TRUE-LIFE of Battery Capacity (Resistance / Voltage / Current & Temperature) Simultaneously
- Measure battery charge / discharge capacity (Ah)
- Measure battery State of Charge SOC (%)
- On-line Testing without shutting down battery
- Built-in Comparator Function
- Rates Conditions as PASS, WARNING or FAIL
- Auto Datalogging Micro SD Card 4GB upto 99 blocks
- Compact and lightweight
- USB Interface & Software
- Load Test Analysis (Charge / Discharge)
- Auto-Hold & Auto-Data Storage
- Wide Range 0 ~ 1200 Ah
- Auto Power Off
- Memory & Read Function

Specifications

Battery Types Tested	UPS Battery, Motor Cycle (6V/12V : 2 ~ 20Ah), Car (12V : 21 ~ 80Ah), Truck (12V : 83 ~ 160Ah) Household Appliances [(9V : upto 625 mAh), (AA : upto 2850 mAh), (AAA : upto 1250 mAh), (C : upto 8350 mAh), (D : upto 20500 mAh)], Lithium Notebook Battery : [(14.8V : 3600 ~ 4800 mAh), (11.1V : 3600 ~ 7200 mAh)], Lithium Digital Camera Battery : (3.7V : 650 ~ 1350 mAh), Lithium Cordless Phone Battery : (3.7V : 800 ~ 1250 mAh),
Battery Capacity	0 to 1200Ah
Resistance	Ranges : 4mΩ, 40mΩ, 400mΩ, 4Ω, 40Ω, 400Ω Resolution : 1μΩ, 10μΩ, 100μΩ, 1mΩ, 10mΩ, 100mΩ Accuracy : ± (0.8% reading + 6 digits) on all ranges. except ± (3% reading + 20 digits) on 4mΩ
Measurement Condition	Current : Approx. 40mA, 4mA, 400μA, 40μA, 4μA Frequency : 1KHz ± 30Hz
DC Voltage	Range : 6V, 60V; Resolution : 1mV, 10mV; Accuracy : ±(0.1% reading + 6 digits)
Temperature	Range : -20°C to 60°C (-4°F to 140°F); Resolution : 0.1°C / 0.1°F; Accuracy : ± 1°C / ± 1.8°F
DC Current	Range : 600A; Resolution : 0.1A; Accuracy : ± (2%rdg + 2dgt)
Open Circuit Voltage	5V max
Datalogging	Manual Datalogging : 999 Sets (Can be read by Meter & Download by PC) Auto Datalogging : Micro SD card 4GB (Max. 99 Blocks)
Comparator	Setting : Resistance Upper and Lower Limits and Voltage (Threshold) Upper and Lower Limit Memory : 99 Sets of Values
Operating Environment	0°C to 40°C (32°F to 104°F), 80% RH or less, Non-condensing
Power Supply	Six 1.5V AA size Alkaline Batteries
Battery life	5.5 Hours
Standard	IEC 61010-1, 1000V Insulation CAT III, Pollution Degree 2
Dimensions / Weight	198 x 94 x 49 mm (approx.) / 530 gms Including Battery (approx.)
Accessories	Alligator Clip Type Test Lead with Temperature Sensor x1, Pin Type Test Lead x 1, DC Current Adaptor x 1, Zero Adjustment Board x 1, Instruction Manual x 1, AA 1.5V Batteries x 6, AC Adaptor x 1, 4GB Micro SD Card (installed) x 1, USB Cable x 1, PC Software Disk x 1 & Carrying Bag x 1