



940K



Brake Fluid Tester

Specifications	Range	Resolution
Brake Oil Type	DOT3 / DOT4 / DOT5.1	
Brake Oil Status Test	GOOD	Water Content < 1%
	CAUTION	Water Content < 3%
	STOP	Water Content > 3%
Auto Ranging	Yes	
Data Hold	Yes	
Backlight	Yes	
Work light	Yes	
Magnet Function	Yes	
Warning Tone	Yes	
Auto Power Off	Yes	
Low Battery Indicator	Yes	
Power	1.5V AAA x 2 Batteries	
Operating Altitude	< 2000m	
Operating Temperature	-10°C ~ +50°C	
Storage Temperature	-20°C ~ +60°C	
Operating Humidity	< 80% RH	
Weight	250gms Including Battery (approx.)	
Dimension	350 (with probe) x 40 x 27mm (approx.)	
Accessories	Carrying Case, Inst. Manual, 1.5V AAA x 2 Batteries (Installed)	

950K



Combustible Gas Leak Detector

Specifications	Range	Resolution	Accuracy
Combustible Gas	0 ~ 999.9 ppm	0.1 ppm	≤10% FS (Methane)
	1000 ~ 9999 ppm	1.0 ppm	
	0 ~ 20.00% LEL	0.01% LEL	
Auto Ranging	Yes		
Sensitivity	≤50 ppm (Methane)		
Response Time	≤2 Seconds		
Warm-up time	30 Sec (approx.)		
Refresh Rate	400 ms		
Flexible Probe	16 inch		
Min / Max / Avg	Yes		
Unit	ppm, %LEL		
Data Hold	Yes		
Backlight	Yes		
Auto Power Off	Yes		
Low Battery Indicator	Yes		
Power	1.5V AAA x 2 Batteries		
Operating Altitude	< 2000m		
Operating Temperature	-10°C ~ +50°C		
Storage Temperature	-20°C ~ +60°C		
Operating Humidity	< 80% RH		
Weight	300gms Including Battery (approx.)		
Dimension	420 (with probe) x 40 x 27mm (approx.)		
Accessories	Carrying Case, Inst. Manual, 1.5V AAA x 2 Batteries (Installed)		