





PFT



MECO AC Power Factor Transducers measure the Power Factor in 1 Phase and 3 Phase electrical systems. The resulting output signal is directly proportional to the system power factor. These Transducers provide an output which is load independent and isolated from the input. The output can be connected to Controllers, Data-Loggers, PLC's, Analog / Digital Indicators, Recorders for display, analysis or control. They are ideal for SCADA, Energy Management, Telemetry for Remote, Local as well as Central Monitoring Systems.

Type	DIN Series	Accuracy
1Phase 1Element 2Wire - Zero Crossing	PFT11	±0.5% of Span
3Phase 1Element 2Wire (Balanced) - Zero Crossing	PFT31	
3Phase 2Element 3Wire (Balanced & Unbalanced) - TRMS	PFT33-TRMS	
3Phase 3Element 4Wire (Balanced & Unbalanced) - TRMS	PFT34-TRMS	

AC Input		DC Output				Auxiliary Power Supply		
Input Voltage	63.5/110/230/440 V (any one only)	Current		Voltage		Tolerance (± 20 %)		Burden
Input Current	1/5 A (any one only)	Output	Load	Output	Load	AC Linear Power Supply	110 V	< 4 VA
Input Frequency	50/60 Hz (any one)	0-1 mA	0-10 KΩ	0-1 V	> 1 kΩ		230 V	
Input PF Range	0.5 (Lag) -1.0 - 0.5 (Lead)	0-5 mA	0-2 KΩ	0-5 V	> 5 kΩ	DC	24 V	
Measuring Range	0.8Un~1.2Un, 0.2In~1.2In	0-10 mA	0-1 KΩ	1-5 V				
Overload (continuous)	2 x In and 1.2 x Un	2-10 mA		0-10 V	>10 kΩ			
Burden (Voltage)	< Un x 6mA/Phase < 6 VA for Self Powered	0-20 mA	2-10 V					
Burden (Current)	< 0.5VA / Phase	4-20 mA						
						Self Powered	Max. Variation of ±20% allowed in Input Voltage	Refer Input Burden

Optional

- Above Input Ranges with suitable CTR/PTR also available
- Bi-directional inputs for Import / Export of Power

Optional

- Dual Non-Isolated Outputs
- Dual Symmetrical & Asymmetrical Outputs
- Bi-directional Outputs

Optional


- Other Auxiliary Power Supplies available subject to technical feasibility

Dimension


DIN Series : ■ Case Size III

Note : ■ For Details refer General & Technical Specifications Page


Connection Diagram




PFT11



PFT31



PFT33



PFT34

Specifications

Accuracy	± 0.5% of Span (standard) Others on request (optional)	Warm Up Time	20 min. (approx.)
Accuracy Range	0 to 120%	Dielectric Strength	2.5kV at 50 Hz for 1 min.(Standard) 4kV (Optional), across Casing - Input/Output/Auxiliary Input - Output Input - Auxiliary Output - Auxiliary
Zero Adjustment	± 2% of Span (min.)	Impulse Test	5kV, 1.2 / 50µS
Span Adjustment	± 10% of Span (min.)	Casing	DIN Series Flame Retardant, Polycarbonate (UL 94V-0) Self Extinguishing, Non Drip, DIN Rail cum Wall Mounting Casing
Response Time	< 250 ms for 0 to 90% of Output < 1 s for 0 to 90% of Output for PF	Applicable Standards	IEC 688 / EN 60688 Electrical Measuring Transducers for converting AC Electrical Quantities to Analog or Digital Signals EN 61010-1 Safety requirements for Electrical Equipment for Measurement Control & Laboratory use EN 61326-1 Electrical Equipment for Measurement Control & Laboratory use - EMC requirements IS12784 (Part-1)1989 Electrical Measuring Transducers for converting AC Electrical Quantities into DC Electrical Quantities : General Purpose Transducer
Output Ripple	< 0.5% of Full Scale		
Compliance Voltage	12VDC (max.)		
Overload -Continuous	Voltage : 1.2 x Un Current : 2 x In		
Overload -Short Duration (1 sec.)	Voltage : 2 x Un Current : 20 x In (one time)		
Max. Open Circuit Voltage	< 30VDC		
Stability	± 0.25% Per Annum, Non Cumulative		
Environmental Conditions	As per IEC 688 User Group II		
Operating Temperature	0 to 55°C, RH < 95% (non condensing)		
Storage Temperature	-20 to 70°C, RH < 95% (non condensing)		
Calibrated At	27°C ± 5°C		
Temperature Coefficient	0.02% / °C		
Isolation	Complete (Input/Output/Auxiliary/ Case)		
Insulation Resistance	>100MΩ at 500VDC		
Self Powered (optional)	Max.Variation of ± 20% in input voltage		

Ordering Information

Model, Input Range, Input Voltage, Input Current, PTR, CTR, Frequency, Auxiliary Supply, Output 1, Output 2 & Optionals

Dimensions (in mm)

